

# **Product Specification**

**UK Model No. - PLF3CMY**



WATER COOLERS

## COMPACT ON-A-WALL



### Models

- PLF3CM delivers 2.5 gph of chilled drinking water.
- PLF5CM delivers 4.7 gph of chilled drinking water.
- PCM is a non-refrigerated fountain.

### Standard Features

- ▶ Waterways Are Lead-Free in Materials & Construction
- ▶ Dial-A-Drink® Bubbler
- ▶ Stainless Steel Top
- ▶ Welded, Heavy-Gauge Steel Frame
- ▶ High-Efficiency Cooling Tank and Coil
- ▶ Refrigerant 134a
- ▶ Limited 5-Year Warranty

### Installation

- ▶ Prior to roughing-in, consult local, state and federal codes for proper mounting height
- ▶ Shipped with complete instructions and wall mounting bracket
- ▶ Removable panels provide easy access for installation

### Colors

- Standard cabinet finish: Sandstone Vinyl-on-Steel
- Optional finishes at no extra cost: Vinyl-on-Steel
- Optional finishes at extra cost: Stainless Steel and Baked Enamel
- Specify finish \_\_\_\_\_

**Limited 5-Year Warranty** (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

*Components in these water coolers/fountains are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.*



*Models covered by these specifications comply with all known Plumbing Codes. Listed by Underwriters' Laboratories. Certified by Canadian Standards Association.*

**Export Warranty:** One year on the sealed refrigeration system and most component parts. Four-year replacement contract on sealed refrigeration system. Detailed warranty certificate enclosed with each water cooler; sample copy available upon request.

Model	50° F Drinking Water 90° F Ambient Air Temp.		Pre-Cooler	Hot 'N Cold Model	115 Volts, 60 Hz			Glass Filler Acc. Option	Cabinet Color Option	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH			Compr. HP	Full Load Amps	Rated Watts			
PLF3CM**	2.5	2.5	No	No	1/8	2.1	160	No	Yes	49 Lbs.
PLF5CM**	4.7	2.5	Yes	No	1/8	2.1	160	No	Yes	51 Lbs.
PCM	Fountain Only							No	Yes	24 Lbs.

Rating Condition 80° F inlet water temperature.

\*\*Special export models available, operable on 220-240 volts, 50 Hertz. UL and CSA certification not applicable.

Specifications are subject to change without notice.

